Benefits

- Large range of self-locking shacklesHead of shackle pin locked into one of the
- Avoids accidental release due to vibrations
 Available in various versions to suit many applications
- Forged in 316L stainless steel

Designed and made in France								
N°	Part	Ø	А	В	W.L.	B.L.	Weight	
	#	mm	mm	mm	Kg	Kg	Kg	
Se	elf-loci	king D sha	ckles					
1	1201	4	13	8	320	700	0.007	
	1202	5	16	10	400	1000	0.013	
	1203	6	20	12	600	1600	0.022	
	1204	8	26	16	1000	2700	0.055	
	1205	10	33	20	1520	4300	0.098	
	1206	12	39	24	2080	6000	0.193	
	1207*	14	47	28	2400	8000	0.312	
Self-locking long shackles								
2	1211	4	22	8	320	700	0.008	
	1212	5	29	10	400	1000	0.017	
	1213	6	33	12	600	1600	0.027	
	1214	8	45	16	1000	2700	0.066	
	1215	10	55	20	1520	4300	0.128	
Self-locking twisted shackle								
3	1222	5	26	10	480	1100	0.016	
	1223	6	30	12	600	1500	0.027	
	1224	8	40	16	1000	3000	0.067	
	1225	10	50	20	1440	4500	0.127	
	ILLS	10	30	20	1110	1500	0.127	
Se	elf-loc	king bow	shackles					
4	1241	4	18	8	320	700	0.009	
	1242	5	23	10	400	1000	0.017	
	1243	6	28	12	600	1500	0.030	
	1244	8	37	16	1000	2700	0.068	
	1245	10	47	20	1520	4300	0.137	
	1246	12	55	24	2080	6000	0.233	
	1247*	16	70	32	3200	10000	0.540	
	1248*	20	80	40	4000	15000	1.056	
Se	olf-loc	kina larae	opening s	hackle				
5	1262	5	36	20	256	1100	0.016	
	1263	6	42	25,5	320	1500	0.027	
	1264	8	57	32	768	2700	0.067	
	1265	10	72	40	1280	4000	0.127	
	1203	10	72	10	1200	1000	0.127	
			ackles «D»					
				ick out fron	n the shack	le's body, th	ius elimi-	
	iting ar 1303	ny risk of sn 6	agging. 19	12	600	1600	0.022	
6	1303	8	26	16	960	2700	0.022	
	1304	10	33	20	1440	4300	0.033	
		10	33	24	2080	5500	0.099	
	1306	6	42			1500		
1	1363			25,5	320	1500	0.044	
(specially designed for batten cars)								
Allen head pin shackles «bow»								
The head of the pin does not stick out from the shackle's body, thus elimi-								

Self-locking shackles

« patented »

















nating any risk of snagging.								
7	1343	6	27	12	600	1500	0.029	
	1344	8	37	16	960	2700	0.067	
	1345	10	47	20	1440	4300	0.133	
	1346	12	55	24	2080	6000	0.222	

Tack shackles

These shackles are specially designed for adjustment to the width of

g	oosene	CKS.					
8	1233	6	45	16	520	1500	0.048
	1234	8	59	21	800	2300	0.110