



Available with
Black Housing

Retro Kit available for easy upgrades from previous Capri models.

101731- Retro Kit in White

101732- Retro kit in Black



Capri3 LED Flood/Spreader Light

Building on the huge success of the Caprera line of spreader lights Lumitec is introducing the all-new Caprera3 series. Now with 1,200 lumens, a smaller, more thermally efficient powder-coated die-cast aluminum housing with improved optical beam pattern. But the innovation doesn't stop there, Caprera3 is available with a full-color spectrum RGBW output for infinite color selection options. IP67 compliant and PLI enabled (Poco compatible) on many models and available with white or black housing.

Specifications:

Lumens:	1,200+ (white)
CCT:	5000K
CRI:	70+
Voltage:	10-30vDC
Rated Watts:	12
IP Rating	IP67
Housing	Die-Cast Aluminum

Key Features:

- Available in white, white/blue, white/red and full-color spectrum RGBW.
- Completely water sealed and IP67 compliant.
- Easy Installation – simple 2-wire hook up.
- Innovative butterfly clip mounting system with no exposed fasteners.
- Constructed of marine grade die-cast aluminum and heat tempered glass.
- Over 2,000+ hour of rigorous ASTMB-117 Salt Spray Chamber testing.
- Proudly designed and manufactured in the USA.
- 3 Year warranty on all Lumitec products.

Product Details:

WHITE	BLACK	COLOR OUTPUT	HOUSING	CRI*	CCT*	VOLTAGE	12VDC	24VDC	LUMENS†
101714	101719	White Dimming	White	70+	5000	10-30vDC	1A	0.5A	1,200+ (wht)
101713	101718	White Non-Dimming	White	70+	5000	10-30vDC	1A	0.5A	1,200+ (wht)
101712	101717	Wht/Red Dimming	White	70+	5000	10-30vDC	1A	0.5A	1,200+ (wht)
101711	101716	Wht/Blue Dimming	White	70+	5000	10-30vDC	1A	0.5A	1,200+ (wht)
101710	101715	Spectrum RGBW	White	70+	5000	10-30vDC	1A	0.5A	1,200+ (wht)

* Lumens, CRI & CCT applies only to white light.

† Integrating sphere measured lumens within 1 minute of initial startup

Features:



Lumen Output



Power Line Instruction



Timed Toggle Protocol



Third Party Dimmer



Color Match Commitment



2-Wire Hookup



Dimming



3 Year Warranty



Certifications:



IP Rated



European Conformity

Ph. + (561) 272-9840 | lumiteclighting.com



Beam Pattern:

Capri3 - LED Flood/Spreader Light

Capri3 - Flood Pattern

Illuminance at a Distance			
	Center Beam fc	Beam Width	
8.3ft	18.1 fc	6.8 ft	15.3 ft
16.7ft	4.47 fc	13.7 ft	30.7 ft
25.0ft	1.99 fc	20.5 ft	46.0 ft
33.3ft	1.12 fc	27.3 ft	61.2 ft
41.7ft	0.72 fc	34.2 ft	76.7 ft
50.0ft	0.50 fc	41.0 ft	92.0 ft

■ Vert. Spread: 44.6°
■ Horiz. Spread: 85.2°

Illuminance at Distance



Iso Candela Plot

Dimensions:

- Width: 4.08in (10.36cm)
- Height: 1.39in (3.53 cm)
- Depth: 1.43in (3.63cm)

