

# **AQUA VOID CARTRIDGE BILGE PUMP**

FEATURES	BENEFITS	COMPETITIVE ADVANTAGES
High Flow Impeller Design	Heightened Efficiency and an Increased Flow Rate	Most Efficient and Highest Flow in GPH Capacity Category
Quick-Change Motor Connection	Enjoy Quick and Hassle-Free Cartridge Motor Changes or Capacity Upgrades	Industry First and Only Cartridge Motor Pump with included harness connection requiring no cutting and splicing of wires
Durable Thermoplastic Housing Design Commonality with Removable Motor Cartridge	Common Body Allows Interchangeable Motor Cartridge Replacement to the Same or Different Size	Upgradeable Cartridge Motors
Water-Cooled Motor, 316 Stainless Steel Shaft and Permanently Lubricated Double Bearings	Corrosion Resistant and Extended Life	
Check Valve	Reduces Cycling from Water Back Flow	
Straight or 90-Degree Dura Port Discharge Ports	Allow Multi-Directional Hose Routing and Eliminate Stress Cracking without Disengaging Hoses or Removing Pump	
Molded T-Slot	Easy Installation with Switches	
Clip-In Basket	Ease of Installation & Maintenance	Π //
<b>AVAILABLE SIZES</b> 500 GPH 12V 800 GPH 12V		



#### **TECHNICAL SPECIFICATIONS**

## Aqua Void Cartridge Bilge Pump: Non-Automatic Submersible Bilge Pumps

PART PUMP		DESCRIPTION	CAPACITY STRAIGHT (12V)		VOLTAGE	AMP	FUSE	HOSE
NUMBER SIZE	GPH		L/MIN	7.521.402	A	SIZE	CONN.	
10-13626-01	500	Aqua Void	000	00	401/	0.54	0.5.4	0/4"
10-13635-01	GPH 3635-01	Aqua Void Automatic - Ultima Combo	600 38		12V	2.7A	3.5 A	3/4"
10-13626-05	800	Aqua Void	795	50	12V	3.7A	5 A	3/4"
10-13636-01	GPH	Aqua Void Automatic - Ultima Combo						

#### **Pump Dimensions**

PUMP SIZE	DESCRIPTION	WIDTH (A)	HEIGHT (B)	LENGTH (C)	WEIGHT
500 GPH	Anna Vaid	70mm	119mm (4.69")	133mm (5.24")	0,32kg (11.2oz)
800 GPH	Aqua Void	(2.75")			0,36kg (12.6oz)
500 GPH	Acus Void Automotic Illhims Combo	75mm (2.95")	120mm (4.69")	168mm (6.63")	0,48kg (17.1oz)
800 GPH	Aqua Void Automatic - Ultima Combo				0,52kg (18.5oz)



Dimensions include straight fitting installed.

## Standard Features: All Cartridge Pumps

	<u> </u>			
BODY	ABS	DURA PORT	PA66/GF - Nylon	
SHAFT 316 Stainless Steel		SHAFT SEAL	Nitrile Rubber	
MOTOR CARTRIDGE	PC-ABS	WIRE SIZE	16 GA, TAC	





Cartridge Motor: Replacement Cartridge

_		
PART NUMBER	PUMP SIZE	DESCRIPTION
09-36336-01	500 GPH	Aqua Series Replacement Cartridge Motor
09-36336-06	800 GPH	Aqua Series Replacement Cartridge Motor



# **SPXFLOW®**

SPX FLOW, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. The green ">" is a trademark of SPX FLOW, Inc.

For more information, visit www.spxflow.com/johnson-pump-marine