
Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Diamond pad eye - Round - Length: 98 mm - M8 screw

Part #6646





Description

Mechanical resistance versus corrosion resistance ratio
Optimized dimensions
For ropes and webbings
For M8 screw
W.L 1 (90°) : 4200 Kg
W.L 2 (45°) : 4200 Kg
W.L 3 (0°) : 4100 Kg
B.L 1 (90*) : 11200 Kg
B.L 2 (45°) : 11200 Kg
B.L 3 (0°) : 11000 Kg

Applications

Multi-Uses :
Mast foot blocks Reefing blocks
Various fastenings

Technical information

	Materials	Duplex stainless steel grade
	Working load (kg)	4200
	Breaking load (kg)	11200
	Weight (g)	250
	A (mm)	98
	B (mm)	73
	C (mm)	59
	D (mm)	35
	E (mm)	22
	F (mm)	27

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2020-2025